

Item	Unit	AuARC 200
Weight	kg	5.5
Power Supply	V/Hz	230
Input Current	А	39
Rated Input Capacity	kVA	8.7
Output Current	А	20 - 200
OCV	V/Hz	70
Rated Output	%	35% at 200
Electrode / Wire Diameter	mm	up to 3.2

Auweld AuARC 200

Compact welder at 7kg with the portability and dependability you'll need out at site. Welds up to 3.2mm electrode, 7kg worth of pure welding power for excellent site performance



Processes

Stick (SMAW)

Features

- IGBT Technology For savings in electricity and improvement in weld quality
- Digital Meter For accurate readings
- Overheat Sensor Protects your machine from thermal shock
- Wind Tunnel Design For efficient heat dissipation

Optional accessories



MAKO Gloves

Consumables



BLUE-ARC 3R BLUE-ARC 16


* Please consult our sales representative for more information

Inclusive accessories





Welding Lead (3m)



Hand Brush



Auweld International Pte Ltd 1 Shipyard Boad, Singapore 6281

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com





Item	Unit	AuARC 250
Weight	kg	6.2
Power Supply	V/Hz	230
Input Current	А	43
Output Current	А	30 - 230
OCV	V	78
Rated Output	% at A	60% at 230
Electrode / Wire Diameter	mm	1.6 - 4.0

Auweld AuARC 250

Reliable yet lightweight STICK/TIG welding machine designed for portability. 230 amps of output is ideal for electrodes up to 4.0mm



Processes

- Stick (SMAW)
- TIG (GTAW) (Strike Arc) ٠

Features


- IGBT Inverter core Gives stable arc, lesser spatter, higher efficiency and energy saving
- Digital Meter For accurate readings •
- Overheat Sensor Protects your machine from • thermal shock
- Overvoltage Protection Protects your machine from unstable voltage supply

Optional accessories



Hammer

Consumables



BLUE-ARC 3R

BLUE-TIG S6

* Please consult our sales representative for more information

Inclusive accessories



Lead (3m)

Ground Lead (3m)



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com





Item	Unit	AuARC 400
Weight	kg	22
Power Supply	V/Hz	415
Input Current	А	35.2
Output Current	А	40 - 400
OCV	V	68
Rated Output	% at A	40% at 400
Electrode / Wire Diameter	mm	1.6 - 6.0

Inclusive accessories





Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuARC 400

Lightweight at 22 kg, this heavy duty machine establishes itself as a reliable, rugged but yet portable machine



Processes

Stick (SMAW)

Features

- IGBT Technology The core adopts advanced IGBT device that gives stable arc, lesser spatter and higher efficiency
- Wider range for input voltage 415V+15%
- Digital Meter To preset and display accurate readings of welding current
- Arc force and Hot start adjustable Easy for striking the arc
- VRD Function Key Safety Feature to protect the welders
- Energy Saving More efficient compared to the traditional SCR machine

Optional accessories





Auto Darkening MAKO Gloves Helmet

Consumables



BLUE-ARC 3R BLUE-ARC 16

* Please consult our sales representative for more information



Auweld	AuAR	C 400S

This shipyard tested lightweight machine is built to withstand power fluctuations and has proven itself to be a reliable and rugged machine fit for any industry.

LIGHTWEIGHT



- Stick (SMAW)
- TIG (GTAW) (Strike Arc)

Features

- Heavy Duty with over voltage protection •
- Arc Force adjustment prevents electrodes from sticking
- Digital Meter To preset and display accurate • readings of welding current
- Operates from a standard 3 Phase, 415V, 32/63A power point

Optional accessories





TIG Torch

Auto Darkening Helmet

Consumables







BLUE-ARC 3R

BLUE-TIG S6

* Please consult our sales representative for more information

Inclusive accessories

Item

Weight

Power Supply

Input Current

Output Current

OCV

Rated Output

Electrode / Wire Diameter





Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com



AuARC 400S

19

415

27

40 - 400

74

35% at 400

1.6 - 5.0

Unit

kg

V/Hz

А

А

V

% at A

mm



Item	Unit	AuARC 500
Weight	kg	26
Power Supply	V/Hz	415
Input Current	А	36.1
Output Current	А	40 - 500
OCV	V	65
Rated Output	% at A	40% at 500
Electrode / Wire Diameter	mm	1.6 - 6.0

Inclusive accessories







Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuARC 500

Lightweight at 26 kg, this multi-process machine fulfils both Stick Welding and Gouging needs. This heavy duty machine is reliable and rugged to meet the yard's requirements for intensive use

HOT)START PROTECT

Processes

- Stick (SMAW)
- Gouging •

Features

- IGBT Technology The core adopts advanced IGBT device that gives stable arc, lesser spatter and higher efficiency
- Versatile with a wider range for input voltage: 415V+15%
- Digital Meter To preset and display accurate readings of welding current
- Arc force and Hot start adjustable Enables easy striking of the arc
- The VRD Function Reduces risk of electric shock •
- · Energy Saving More efficient compared with the traditional SCR machine

Optional accessories






Gouging Torch

Gouging Carbon

Consumables



* Please consult our sales representative for more information





Item	Unit	AuCUT 40
Weight	kg	7.1
Power Supply	V/Hz	230
Input Current	А	28
Rated Input Capacity	kVA	6.4
Output Current	A	20 - 40 (Cutting Current Adjustment Range)
OCV	V	280
Rated Output	% at A	60% at 40
Recommended Cutting Thickness v/ Max	mm	10 (MAX)

Inclusive accessories







Portable and easy to operate, a Plasma Cutter that can fulfil your light duty cutting needs. The AuCUT machine gives you greater efficiency and reliability in your cutting jobs at lower cost

THERMAL LIGHTWEIGHT PROTECT

Processes

Plasma Cutting

Features

- IGBT for greater efficiency and better control
- Max Cutting Thickness 10 mm
- Quality Cutting Thickness 8 mm
- Ultra-portable at 7 kg and dimensions of 460 x 280 x 345 mm

Optional accessories



TIG Gloves

Back View



Inclusive of regulator and gas hose attached

* Please consult our sales representative for more information

Distributed By:



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com





Item	Unit	AuCUT 100
Weight	kg	26
Power Supply	V/Hz	415
Input Current	А	22
Rated Input Capacity	kVA	10.5
Output Current	A	40 - 100 (Cutting Current Adjustment Range)
OCV	V	120
Rated Output	% at A	60% at 100
Recommended Cutting Thickness v/ Max	mm	30 (MAX)

Inclusive accessories





(3m)







Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuCUT 100

A reliable and stably Heavy Duty Plasma cutter to meet industrial cutting needs. This efficient and compact machine enables cutting of thickness up to 30mm



Processes

Plasma Cutting

Features

- IGBT for greater efficiency and better control
- Max Cutting Thickness 30mm •
- Efficient and low consumption for energy and cost savings
- · Fast cutting speeds and less deformation

Optional accessories



TIG Gloves

Back View



Inclusive of regulator attached

* Please consult our sales representative for more information





Item	Unit	AuMIG 500
Weight	kg	84
Power Supply	V/Hz	415
Input Current	Α	41.8
Output Current	А	50 - 500
OCV	V	70
Rated Output	% at A	60% at 500
Electrode / Wire Diameter	mm	1.0 - 1.6

Inclusive accessories





MIG Welding Torch

Ground Control Cable Lead (5m) (5m), Gas Hose and Hose Clamp



ALL YOU NEED FOR WELDING

Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuMIG 500

The serious welder's staple for FCAW and GMAW, the economic combination of consistency and stability. A competitive welder that will help you face the competitive environment in today's competitive times

• THERMAL PROTECT LIGHTWEIGHT

Processes

- MIG (GMAW & FCAW)
- Stick (SMAW)
- TIG (GTAW) (Strike Arc)

Features

- IGBT Inverter For better arc stability
- Overheat Sensor Protects your machine from overheating
- Stepless Heat and Wire speed setting for maximum sensitivity
- Slip-Free 4 roller feeding and easy adjust manual wire feeding
- Integrated Cylinder Rack and detachable feeder for convenient workshop usage
- Digital Display For accurate readings

Optional accessories





Cooler

Regulator (CO₂)

Consumables







BLUEMIG S6 BLUECORE 71T

71T BLUE-TIG S6

BLUE-ARC 3R



Please consult our sales representative for more information

BLUE-ARC 16





Item	Unit	AuPRO 500
Weight	kg	150
Power Supply	V/Hz	415
Input Current	А	41.5
Output Current	A	40 - 500 (GMAW) 60 - 500 (Gouging)
OCV	V	15 - 45
Rated Output	% at A	60% at 500

Inclusive accessories

- Wire Feeder
- **Torch Adaptor**

Optional accessories



MIG Torch



of Differing Length



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuPRO 500

The reliable and multi-functional, highly efficient welding machine specialized for shipbuilding and industrial sectors. A powerful machine that enables an effective weld in many scenarios, including heavy industries and ship building. Proven and tested in the shipbuilding sector, this is a machine to look out for!

• THERMAL PROTECT HOT)START

Processes

- MIG (GMAW & FCAW)
- TIG (GTAW) (Strike Arc)
- Stick (SMAW)
- Air Carbon Arc Gouging (CAC-A)

Features

- Allows for cable extension up to 120m
- Energy Saving Function For power efficiency minimizing power wastage
- Input fluctuation and over current protection circuit protects your machine
- Regulates output in event of load variance for stable arc
- Stable, Made-in-Korea Thyristor based machine

Consumables





BLUE-TIG S6

BLUEMIG S6 BLUECORE 71T



BLUE-ARC 3R BLUE-ARC 16

* Please consult our sales representative for more information





Item	Unit	AuPRO 600
Weight	kg	199
Power Supply	V/Hz	415
Input Current	А	60.8
Output Current	A	50 - 720 (GMAW) 80 - 720 (Gouging)
OCV	V	15 - 52
Rated Output	% at A	100% at 600

Inclusive accessories

- Wire Feeder
- Torch Adaptor

Optional accessories



MIG Torch



Extension Cable of Differing Length (Welding Cable) extension kit



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuPRO 600

The multi-functional, highly efficient welding machine specialized for shipbuilding and structural steel fabricators and offshore fabricators. A powerful machine that enables an effective weld in many scenarios, including heavy industries and ship building. Proven and tested in the shipbuilding sector, this is a machine to look out for!



Processes

- MIG (GMAW & FCAW)
- TIG (GTAW) (Strike Arc)
- Stick (SMAW)
- Air Carbon Arc Gouging (CAC-A)

Features

- Allows for cable extension up to 120m
- Energy Saving Function For power efficiency minimizing power wastage
- 100% duty cycle at 600A
- Input fluctuation and over current protection circuit protects your machine
- Regulates output in event of load variance for stable arc
- Stable, Made-in-Korea Thyristor based machine

Consumables





BLUEMIG S6 BLUECORE 71T

1T BLUE-TIG S6



BLUE-ARC 3R BLUE-ARC 16

* Please consult our sales representative for more information

Auweld AuTIG 200 Pulse



Item	Unit	AuTIG 200
Weight	kg	13
Power Supply	V/Hz	230
Input Current	А	26.8
Output Current	A	TIG: 10 - 180 MMA: 10 - 180
OCV	V	59
Rated Output	% at A	60% at 180
Electrode / Wire Diameter	mm	1.6 - 3.2

Inclusive accessories





5m 200A TIG Welding Torch, Long Cap, #4, #5 Nozzle

Ground Gas Hose Lead (2m)



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

The easy to understand AuTIG 200 Pulse allows for minimal adjustments required while obtaining the ideal performance you'll need for a TIG welder

THERMAL PROTECT ANTI STICKING LIGHTWEIGHT

Processes

- TIG (GTAW)
- Stick (SMAW)

Features

- IGBT Inverter Core Gives stable arc, lesser spatter, higher efficiency and energy saving
- Digital Meter For accurate readings •
- Overheat Sensor Protects your machine from • thermal shock
- High Frequency For easy HF arc start without tungsten or material contamination
- Stepless Setting For accurate setting of your desired amperage
- Postflow Prevents unnecessary contamination at the end of your weld

Optional accessories





(Argon) Electrode

Consumables





BLUE-TIG S6

BLUE-ARC 16

* Please consult our sales representative for more information





Item	Unit	AuTIG 250
Weight	kg	23
Power Supply	V/Hz	230
Input Current	A	34
Output Current	A	5 - 250
OCV	V	21 - 30
Rated Output	% at A	60% at 250
Electrode / Wire Diameter	mm	1.6 - 4.0

Inclusive accessories





200A 5m TIG Welding Torch

Ground Lead (2m)

Dinse Connector Gas Hose And Clamp



Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Auweld AuTIG 250 Pulse

All-encompassing TIG welder which combines durability, performance and value into one complete package



Processes

- TIG (GTAW)
- Stick (SMAW)

Features

- Lightweight @ 23kg allows for use on-site
- Stepless Current For accurate amperage setting
- Digital Meter For accurate readings

Cooler

- Overheat Sensor Protects your machine from thermal shock
- High Frequency For easy HF arc start without tungsten or material contamination
- Postflow Protects the weld and electrode at end of weld, protecting your weld from unnecessary contamination

Optional accessories





Regulator (Argon) Tungsten Electrode

Consumables





BLUE-ARC 16

* Please consult our sales representative for more information

Auweld AuTIG 400 Pulse



Item	Unit	AuTIG 400
Weight	kg	54
Power Supply	V/Hz	380
Input Current	A	26.4
Output Current	A	TIG: 20 - 400 SMAW: 25 - 350
OCV	V	72
Rated Output	% at A	60% at 400

Inclusive accessories





8m TIG Welding Torch

Ground Lead (3m)

8mm Gas Hose (4m), 9 - 16 Hose Clamp - 2pc



ALL YOU NEED FOR WELDING

Auweld International Pte Ltd

1 Shipyard Road, Singapore 628128 Tel: (65) 6262 6626 • Fax: (65) 6261 2688 Hotline: (65) 6262 3633 Email: enquiry@auweld.com

Heavy duty TIG welding machine meant for users handling large exotic material that require strength and durability to withstand high amperage TIG welding



Processes

- TIG (GTAW) •
- Stick (SMAW)

Features

- IGBT Inverter Core Gives stable arc, lesser spatter, higher efficiency and energy saving
- Digital Meter For accurate readings
- High Frequency Strike start for easy of arc without • tungsten or material contamination
- Stepless Setting For accurate setting of your desired amperage
- Postflow Protects the weld and electrode at end of weld, protecting your weld from unnecessary contamination
- Mobility Wheels for convenient workshop movement

Optional accessories





Regulator (Argon)

Cooler Flectrode

Consumables





Tungsten

BLUE-TIG S6

BLUE-ARC 16

* Please consult our sales representative for more information

BLUE-ARC 3R